How to edit FPM config Older Version Of PHP?(Pending)

FPM (FastCGI Process Manager) is a process manager for PHP that enables the handling of PHP requests through FastCGI. It is commonly used with PHP-FPM, which stands for PHP FastCGI Process Manager. The FPM config file, typically named `php-fpm.conf` or `www.conf`, contains various configuration settings for PHP-FPM.

Tutorial :

You can watch the Video or Continue reading the post.

https://www.youtube.com/embed/6MAJC8YcGb0

Navigate to the Server PHP Dashboard(Use this link to view How to Navigate).

1. Click on the menu icon and Select FPM Configuration Option.

Here, you can see FPM Config.

Edit PHP CLI Configuration:

Click on Edit PHP CLI Configuration.

Click on the dropdown error reporting and select error.

Click on the Pull button.

Here, you can see PHP CLI Configuration Pull Successfully.

Edit PHP CLI Configuration

Basic   Advance

Last Sync: **9 seconds ago**

Pull   Push

Path: **/etc/php/7.4/cli/php.ini**

Completed

Max File Upload Size (in MB)

2

Max File Post Size (in MB)

8

Max File Uploads

20

Memory Limit

512

Max Execution Time

Click on the push button.

Edit PHP CLI Configuration ✕

Basic Advance

Last Sync: **1 minutes ago**

Pull   Push

Path: **/etc/php/7.4/cli/php.ini**

Completed

Max File Upload Size (in MB)

2

Max File Post Size (in MB)

8

Max File Uploads

20

Memory Limit

512

Max Execution Time

Here, you can see PHP CLI Configuration Push Successfully.

Edit PHP CLI Configuration ✕

Basic　　Advance

Last Sync: **2 seconds ago**

Pull　Push

Path: **/etc/php/7.4/cli/php.ini**

Completed

Max File Upload Size (in MB)

2

Max File Post Size (in MB)

8

**Max File Uploads**

20

Memory Limit

512

Max Execution Time

Click on the advance tab button.

Click on the pull button.

Here, you can see PHP CLI Configuration Pull Successfully.

Edit PHP CLI Configuration

Basic   Advance

Last Sync: **2 seconds ago**

Pull   Push

Path: **/etc/php/7.4/cli/php.ini**

Completed

```
 1  IP]
 2
 3  ;;;;;;;;;;;;;
 4  oout php.ini   ;
 5  ;;;;;;;;;;;;;
 6  HP's initialization file, generally called php.ini, is re
 7  onfiguring many of the aspects of PHP's behavior.
 8
 9  HP attempts to find and load this configuration fr
10  ie following is a summary of its search order:
11  SAPI module specific location.
12   The PHPRC environment variable. (As of PHP 5.2.
13   A number of predefined registry keys on Window
14   Current working directory (except CLI)
15   The web server's directory (for SAPI modules), o
16  itherwise in Windows)
17   The directory from the --with-config-file-path c
18  'indows directory (usually C:\windows)
19  ie the PHP docs for more specific information.
20  tp://php.net/configuration.file
```

Click on the push button

Here, you can see PHP CLI Configuration Push Successfully.

Edit PHP FPM Configuration:

Click on Edit PHP FPM Configuration.

Click on the dropdown Error Reporting.

Edit PHP FPM Configuration ✕

Max File Post Size (in MB)

8

Max File Uploads

20

Memory Limit

128

Max Execution Time

30

Error reporting

▼

☐ Display Errors

☐ Allow URL Include

☑ Allow URL fopen

Selected on the Error

Edit PHP FPM Configuration   ✕

Max File Post Size (In MB)

8

Max File Uploads

20

Memory Limit

128

Max Execution Time

E_ALL (Show all errors, warnings and notices including coding standards.)

E_ALL & ~E_NOTICE (Show all errors, except for notices)

E_ALL & ~E_NOTICE & ~E_STRICT (Show all errors, except for notices and coding standards warnings.)

E_COMPILE_ERROR|
E_RECOVERABLE_ERROR|E_ERROR|
E_CORE_ERROR (Show only errors)

Click on the Pull button.

Here, you can see PHP FPM Configuration Pull Successfully.

Edit PHP FPM Configuration ✕

Basic   Advance

Last Sync: **just now**

Pull   Push

Path: **/etc/php/7.4/fpm/php.ini**

Processing

Max File Upload Size (in MB)

2

Max File Post Size (in MB)

8

Max File Uploads

20

Memory Limit

128

Max Execution Time

Click on the Push button.

Here, you can see PHP FPM Configuration Pupush Successfully.

Click on the tab bar in the Advance button.

Click on the Pull button.

Here, you can see PHP FPM Configuration Pull Successfully.

Edit PHP FPM Configuration ✕

Basic	Advance

Last Sync: **just now**

Pull   Push

Path: **/etc/php/7.4/fpm/php.ini**

Processing

```
1   [PHP]
2
3   ;;;;;;;;;;;;;;;;;;;;
4   ; About php.ini   ;
5   ;;;;;;;;;;;;;;;;;;;;
6   ; PHP's initialization file, generally called php.ini, i
7   ; configuring many of the aspects of PHP's behav
8
9   ; PHP attempts to find and load this configuratio
10  ; The following is a summary of its search order:
11  ; 1. SAPI module specific location.
12  ; 2. The PHPRC environment variable. (As of PHP
13  ; 3. A number of predefined registry keys on Win
14  ; 4. Current working directory (except CLI)
15  ; 5. The web server's directory (for SAPI modules
16  ; (otherwise in Windows)
17  ; 6. The directory from the --with-config-file-pa
18  ; Windows directory (usually C:\windows)
19  ; See the PHP docs for more specific informatior
20  ; http://php.net/configuration.file
```

Click on the Push button.

Here, you can see PHP FPM Configuration push Successfully.

Click on Edit Pool Configuration (default).

Click on the Pull button.

# Edit Pool Configuration (default)

✕

Last Sync: **2 days ago**

Pull   Push

Path: **/etc/php/7.4/fpm/pool.d/www.conf**

Pending

```
1
```

Click on the Push button.

Edit Pool Configuration (default)

✕

Last Sync: **2 seconds ago**

Pull   Push

Path: **/etc/php/7.4/fpm/pool.d/www.conf**

Completed

```
 1   ; Start a new pool named 'www'.
 2   ; the variable $pool can be used in any directive
 3   ; pool name ('www' here)
 4   [www]
 5
 6   ; Per pool prefix
 7   ; It only applies on the following directives:
 8   ; - 'access.log'
 9   ; - 'slowlog'
10   ; - 'listen' (unixsocket)
11   ; - 'chroot'
12   ; - 'chdir'
13   ; - 'php_values'
14   ; - 'php_admin_values'
15   ; When not set, the global prefix (or /usr) applies
16   ; Note: This directive can also be relative to the g
17   ; Default Value: none
18   ;prefix = /path/to/pools/$pool
19
20   ; Unix user/group of processes
21   ; Note: The user is mandatory. If the group is not
```

Looking for mobile App Instructions?

Available at https://kb.cloudpanzer.com/books/web-portal/page/how-to-use-an-older-version-of-php

---